## PATENT COOPERATION TREATY

REC'D 0 9 JAN 2006

WIPO

PCT

# INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY (Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference DSH003	FOR FURTHER ACTION	See Form PCT/IPEA/416			
International application No. PCT/NZ2004/000337	International filing date (day/month/year) 23 December 2004	, , , , , , , , , , , , , , , , , , , ,			
International Patent Classification (IPC) or		23 December 2003			
Int. Cl.	national classification and IPC				
	<b>B65D 88/54</b> (2006.01) <b>B65G 4</b> 7	7/19 (2006.01)			
Applicant Dell exercises as a result of the control					
DSH SYSTEMS LIMITED et al					
1. This report is the international preliminar Authority under Article 35 and transmitted.	ry examination report, established by this In ed to the applicant according to Article 36.	nternational Preliminary Examining			
2. This REPORT consists of a total of 3					
3. This report is also accompanied by ANN					
r	International Bureau) a total of 5 sheets,	as follows:			
sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).					
sheets which supersede earl the disclosure in the interna Box.	lier sheets, but which this Authority conside tional application as filed, as indicated in it	ers contain an amendment that goes beyond em 4 of Box No. I and the Supplemental			
a sequence listing and/or table re	only) a total of (indicate type and number of lated thereto, in electronic form only, as ind 2 of the Administrative Instructions).	of electronic carrier(s)) , containing licated in the Supplemental Box Relating to			
4. This report contains indications relating	to the following items:				
X Box No. I Basis of the report	Basis of the report				
Box No. II Priority		•			
Box No. III Non-establishment	of opinion with regard to novelty, inventive	e step and industrial applicability			
	Lack of unity of invention				
X Box No. V Reasoned statemen citations and explan	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement				
	Certain documents cited				
Box No. VII Certain defects in the	Certain defects in the international application				
<del></del>	s on the international application				
Date of submission of the demand	D. C. Li				
30 May 2005	Date of completion of 03 January 2006	this report			
Name and mailing address of the IPEA/AU	Authorized Officer				
AUSTRALIAN PATENT OFFICE					
PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustralia.gov.au  ASANKA PERERA					
Facsimile No. (02) 6285 3929		Telephone No. (02) 6283 2373			

#### INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/NZ2004/000337

Bo	x No.	Basis of the report					
1.	Wit	regard to the language, this report is based on:					
	X	The international application in the language in which it was filed					
		A translation of the international application into translation furnished for the purposes of:	of a				
		international search (under Rules 12.3(a) and 23.1 (b))					
	*	publication of the international application (under Rule 12.4(a))					
		international preliminary examination (Rules 55.2(a) and/or 55.3(a))					
2.	furn	With regard to the elements of the international application, this report is based on (replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report):					
		the international application as originally filed/furnished	•				
	X	the description:					
		pages 1-14 as originally filed/furnished					
		pages* received by this Authority on with the letter of pages* received by this Authority on with the letter of					
	X	pages* received by this Authority on with the letter of the claims:					
	لثثا	pages as originally filed/furnished					
		pages* as amended (together with any statement) under Article 19					
		pages* 15-19 received by this Authority on 18 November 2005 with the letter of 18 November	2005				
	[ <del></del> ]	pages* received by this Authority on with the letter of					
	X	the drawings:					
		pages 1/5-5/5 as originally filed/furnished  pages* received by this Authority on with the letter of					
		pages* received by this Authority on with the letter of pages* received by this Authority on with the letter of					
		a sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing.					
3.		The amendments have resulted in the cancellation of:					
		the description, pages					
		the claims, Nos.					
		the drawings, sheets/figs	ı				
		the sequence listing (specify):	ļ				
		any table(s) related to the sequence listing (specify):					
	<del></del>		i				
4.		This report has been established as if (some of) the amendments annexed to this report and listed below had not been ade, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Fig.2(c)).	n Kule				
		the description, pages					
		the claims, Nos.					
		the drawings, sheets/figs					
		the sequence listing (specify):	ļ				
		any table(s) related to the sequence listing (specify):					
•	If item 4 applies, some or all of those sheets may be marked "superseded."						

### INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

Claims

International application No.

YES

NO

PCT/NZ2004/000337

I			= = = = = = = = = = = = = = = = = = = =	
Box No. V	Reasoned statement u citations and explanat	nent under Article 35(2) with regard to novelty, inventive step or industrial applicability; planations supporting such statement		
1. Statement	t			
N	lovelty (N)	Claims 1-19	YES	
		Claims	NO	
Inventive step (IS)	Claims 1-19	YES		
_		Claims	NO	
Industrial applicability (IA)	Claims 1-19	V/ES		

#### 2. Citations and explanations (Rule 70.7)

The cited prior art in the International Search Report do not disclose or fairly suggest an apparatus, a computer controlled process or a method as defined by independent claims 1, 11 and 15 respectively.

Therefore the subject matter of these claims and appended claims is new and meets the requirements of Article 33(2) PCT with regard to novelty.

The claimed invention is not obvious in the light of any of the cited documents nor is it disclosed in any obvious combination of them. It is also considered that it would not be obvious to a person skilled in the art in the light of common general knowledge either by itself or in combination with any of these documents.

Therefore the subject matter of these claims is not obvious and meets the requirements of Article 33(3) PCT with regard to inventive step.

#### CLAIMS:

- 1. A material discharge apparatus for controlling the discharge of flowable material being conveyed through a conical shaped hopper, the material to be continually discharged through the hopper until in feeding is stopped or ends, the hopper being 5 configured and arranged, in use, to be operable at a height above a surface on which a discharge pile is to be formed, the apparatus including the hopper having an inlet opening adjacent the top and an open discharge outlet at the base of the hopper, the discharge outlet being exposed to the surrounding environment such that, in use, 10 flowable material is discharged through the open discharge outlet, and a valve means being configured and arranged in the hopper, the valve means including a bulb having a lower end portion positionable adjacent the discharge outlet forming a gap between the inner wall of the hopper and the bulb for material, in use, to flow by being gravity fed therebetweenand out through the open discharge outlet, the valve means and/or 15 the hopper being adapted to move relative to the other, in use, for controlling the rate of continual discharge through the gap to form a solid column of flowing material to reduce the amount of dust being dispersed into the surrounding environment.
- 2. A material discharge apparatus according to claim 1 wherein the valve means is arranged in the hopper such that the lower end portion adjacent the discharge outlet is substantially centrally positioned such that the gap between the hopper and the valve means is evenly spaced about the lower end portion of the valve means, and wherein the discharge outlet is not closed by the valve means.
- A material discharge apparatus according to claim 1 wherein the hopper is adapted to be suspended below a support frame by hopper support members, and wherein the valve means is adapted to be suspended below the support frame.
- A material discharge apparatus according to claim 3 wherein the hopper is adapted to be suspended below a support frame by a plurality of spaced apart hopper support members, the hopper support members being elastic in form, in use, to expand under

the weight of material being conveyed through the hopper so as to increase the gap between the hopper and the valve means to increase the flow of material therethrough.

- 5 5. A material discharge apparatus according to claim 1 wherein the valve means includes a bulb having a lower end portion having a circular cross section, and wherein the hopper has a circular cross section that is tapered toward the discharge outlet.
- A material discharge apparatus according to claim 1 wherein the hopper is adapted to be attached to a support frame and being adapted with a load cell transducer means configured and arranged to measure the weight of the hopper and generate a measurement signal that is forwarded to a valve control means, and a valve height adjustment means configured and arranged for attachment to the valve means and being electrically connected to the valve control means and to receive command signals therefrom, the valve control means being adapted to receive, in use, a measurement signal from the transducer means and control movement of the valve means by the valve control means to raise and lower the valve means to increase or decrease the gap respectively between the hopper and the valve means.

7. A material discharge apparatus according to claim 6 wherein the valve control means includes a computer controller means programmed by a suitable computer program for controlling the operation of the valve height adjustment means, the controller means allowing a user to enter a preset weight setting for the hopper, and in use, the controller means receives a digital measurement signal from the load cell means representing the weight of the hopper with material, and when the weight signal exceeds the threshold preset weight setting the controller means actuates the valve height adjustment means to raise the valve means to increase the gap and allow a higher discharge rate of material until the weight measurement signal from the load cell means falls below the preset weight setting.

20

- 8. A material discharge apparatus according to claim 6 wherein the controller means actuates the valve height adjustment means to raise the valve means in predetermined incremental lift positions.
- 5 9. A material discharge apparatus according to claim 1 wherein the hopper is made of a rotary moulded plastics material.
- 10. A material discharge apparatus according to claim 3 wherein the hopper support members include coil springs, in use, that are expandable under the weight of lading in the hopper.
  - 11. A computer controlled process for controlling the flow rate of material conveyed through a hopper, the computer program including the steps of:
- a. receiving a measurement signal from a load cell transducer means representing an actual measurement of weight of a hopper with material flowing therethrough and comparing the measurement against a preset measurement of weight representing a preferred flow rate through the hopper;
- b. if the actual measurement of weight is more than the preset measurement of weight a control signal is sent to a valve height adjustment means to lift a valve means in the hopper to increase the discharge rate of material flowing through the hopper;
  - c. if the actual measurement of weight is less than the preset measurement of weight a control signal is sent to the valve height adjustment means to lower the valve means in the hopper to decrease the discharge rate of material flowing through the hopper; and
  - d. resetting the program to repeat step a until the material has been discharged through the hopper.

25

- 12. A computer controlled process according to claim 11 wherein in step a, the program allows an operator to preset the number of measurements per minute taken by the load cell transducer means.
- 5 13. A computer controlled process according to claim 11 wherein in step a. if the actual measurement of weight is determined by the program to be the same as the preset measurement of weight the program will reset to step a.
- 14. A computer controlled process according to claim 11 using the apparatus of claim 6.
  - 15. A method of controlling the flow rate of material conveyed through a hopper, the steps of the method including:
    - A. Comparing an actual measurement of weight of a hopper with material flowing therethrough with a preset measurement of weight representing a preferred flow rate through the hopper;
      - B. if the actual measurement of weight is more than the preset measurement of weight, the valve means in the hopper is actuated to rise to increase the discharge rate of material flowing through the hopper;
- 20 C. if the actual measurement of weight is less than the preset measurement of weight the valve means in the hopper is actuated to lower the valve means in the hopper to decrease the discharge rate of material flowing through the hopper; and
  - D. repeating step a until the material has been discharged through the hopper.
- A material discharge apparatus according to claim I wherein the bulb includes a conical lower end portion, and a conical top portion with a circular cross section being tapered toward the top end portion forming an inverted cone on the lower end portion, the conical lower end portion being tapered toward the lower end of the bulb.
- 30 17. A material discharge apparatus substantially as herein described with reference to any one of the accompanying drawings.

10

15

- 18. A computer controlled process according to claim 11 substantially as herein described.
- 5 19. A method of controlling the flow rate of material conveyed through a hopper according to claim 15 substantially as herein described.